SPECIFICATIONS






Vehicle	UV34 Diesel	UV34XL Diesel	UV34 Gas	UV34XL Gas
Engine				
Engine Model	Diesel	Diesel	1000cc Dual	1000cc Dual
Engine Cooling	Liquid	Liquid	Liquid	Liquid
Emissions Tier (EPA)	Tier 4	Tier 4	-	-
Engine Fuel	Diesel	Diesel	Gasoline EFI	Gasoline EFI
Horsepower	24.5 hp (18.2 kW)	24.5 hp (18.2 kW)	39.9 hp (29.7 kW)	39.9 hp (29.7 kW)
Displacement	55.0 cu. in. (0.9 L)	55.0 cu. in. (0.9 L)	61.0 cu. in. (1.0 L)	61.0 cu. in. (1.0 L)
Performance				
Operating Weight	1935 lb. (878 kg)	2165 lb. (982 kg)	1855 lb. (841 kg)	2085 lb. (945 kg)
Travel Speed - High	35.0 mph (56.3 km/hr.)	35.0 mph (56.3 km/hr.)	35.0 mph (56.3 km/hr.)	35.0 mph (56.3 km/hr.)
Travel Speed - Low	16.0 mph (25.0 km/hr.)	16.0 mph (25.0 km/hr.)	25.0 mph (40.0 km/hr.)	25.0 mph (40.0 km/hr.)
Travel Speed - Reverse	16.0 mph (25.0 km/hr.)	16.0 mph (25.0 km/hr.)	25.0 mph (40.0 km/hr.)	25.0 mph (40.0 km/hr.)
Capacities				
Fuel Tank	11.5 gal. (43.5 L)	11.5 gal. (43.5 L)	11.5 gal. (43.5 L)	11.5 gal. (43.5 L)
Cargo Box Length	43.5 in. (1105 mm)	43.5 in. (1105 mm)	43.5 in. (1105 mm)	43.5 in. (1105 mm)
Cargo Box Width	54.0 in. (1372 mm)	54.0 in. (1372 mm)	54.0 in. (1372 mm)	54.0 in. (1372 mm)
Cargo Box Bed Load Capacity	1250 lb. (567 kg)	1250 lb. (567 kg)	1250 lb. (567 kg)	1250 lb. (567 kg)
Cargo Box Height	11.5 in. (292 mm)	11.5 in. (292 mm)	11.5 in. (292 mm)	11.5 in. (292 mm)
Cargo Box Bed Load Height	38.0 in. (965 mm)	38.0 in. (965 mm)	38.0 in. (965 mm)	38.0 in. (965 mm)
Vehicle Rated Capacity*	1900 lb. (862 kg)	2075 lb. (941 kg)	1900 lb. (862 kg)	2075 lb. (941 kg)
Dimensions				
Length	123.0 in. (3124 mm)	155.0 in. (3937 mm)	123.0 in. (3124 mm)	155.0 in. (3937 mm)
Width	62.0 in. (1575 mm)	62.0 in. (1575 mm)	62.0 in. (1575 mm)	62.0 in. (1575 mm)
Height	76.0 in. (1930 mm)	76.0 in. (1930 mm)	76.0 in. (1930 mm)	76.0 in. (1930 mm)
Ground Clearance	11.7 in. (296 mm)	11.7 in. (296 mm)	11.7 in. (296 mm)	11.7 in. (296 mm)
Turning Radius	110.0 in. (2794 mm)	154.0 in. (3911 mm)	110.0 in. (2794 mm)	154.0 in. (3911 mm)
Features				
Under-Seat Storage	Std	Std	Std	Std
Seat Belt	3-point, Retractable	3-point, Retractable	3-point, Retractable	3-point, Retractable
Power Steering	Std	Std	Std	Std
ROPS Approval	Std	Std	Std	Std
EVAP (California only)	Opt	Opt	Opt	Opt
Hour Meter	Std	Std	Std	Std
Speedometer	Std	Std	Std	Std
Tilt Steering Wheel	Std	Std	Std	Std
Bed Lift (manual)	Std	Std	Std	Std
Frame Type	Steel	Steel	Steel	Steel
Receiver Hitch	2.0 in.	2.0 in.	2.0 in.	2.0 in.
Front Suspension	Independent	Independent	Independent	Independent
Rear Suspension	Independent	Independent	Independent	Independent
Headlights	Std	Std	Std	Std
Drive System				
Transmission Type (CVT)	P-R-N-L-H	P-R-N-L-H	P-R-N-L-H	P-R-N-L-H
Traction Type	4x4	4x4	4x4	4x4
4WD Selection	Switch	Switch	Switch	Switch
Differential Lock	Switch	Switch	Switch	Switch

*Vehicle rated capacity includes cargo box load, weight of occupant(s) and the weight of any accessories.