

DOOSAN

Articulated Dump Truck

DA30/DA45

Maximum power (ISO 3046)	375 / 500 HP
Maximum payload	28 m t (31 st) / 41 m t (45 st)
Body capacity heaped (With tailgate)	17.8 / 26.1 m ³



TAKE A TOUR OF THE DA30

DA30
DA45

PRODUCTIVITY

The DA30 offers best-in-class ground clearance & ground bearing pressure. Combined with superior torque at low engine RPM, and superior power and traction, we offer you the best productivity.

OPERATOR'S ENVIRONMENT

Ergonomic controls, most spacious cab in the market, high-class seat, Bluetooth radio with USB, and much more...

OPERATE AT EASE

Upgraded monitor panel, new control panel for more convenient use, real-life payload meter with external light indication, rear-view camera, body tip boost button, etc.

POWER

Scania DC 09 engine: 276 kW (375 HP) at 2100 rpm with electronic exhaust brake.

NEW QUALITY OF RIDE

New self-leveling, hydro-gas suspension supports soft ride in harsh conditions.

MANEUVERABILITY

Unique design of rear frame, body, and front-mounted differential on transmission make the Doosan machine the most compact ADT in its class, which results in smallest turning radius and outstanding stability.

DIFFERENTIAL

Front and rear differentials are limited slip, longitudinal differential can be manually locked by pushing 1 button.



SAFETY HIGHLIGHTS

Gradient meter with body flip-over protection, Body Over Centre of Gravity function, fenders and hand rails all around cab, superior stability and always visible and clean front cab access.

BODY

Steel plates with 400 HB hardness. Capacity without/with tailgate : 16.8/17.8 m³. Tailgate, body heating & wear plates available as optional equipment.

DOOSAN **CONNECT** TELEMATICS

Monitor your fleet online. As standard, Doosan Connect system with dual mode (satellite, GSM). Check productivity, fuel consumption, system warnings, maintenance status, etc.

BRAKE SYSTEMS

Oil-cooled wet disc brakes (lifetime up to 15,000 hours). Standard hydraulic transmission retarder & hydraulic parking brake.



SERVICE ACCESSIBILITY

Diesel, AdBlue and grease (for auto-lube system) filling from ground level. Easy access to filters and oil filling points. Tilt cab with self-positioning locking mechanism.

* The above image may differ from the actual product.

TAKE A TOUR OF THE DA45

DA30
DA45

PRODUCTIVITY

The Doosan DA45 offers the best combination of payload and efficiency in its class. Thanks to its unique design, best productivity is delivered in all working conditions.

OPERATOR'S ENVIRONMENT

Ergonomic controls, most spacious cab in the market, high-class seat, Bluetooth radio with USB, and much more...

OPERATE AT EASE

Upgraded monitor panel, new control panel for more convenient use, real-life payload meter with external light indication, rear-view camera, body tip boost button, etc.

POWER

Scania DC 13, water-cooled, diesel engine with turbo charger and air to air intercooler engine: 368 kW (500 HP) at 2100 rpm.

NEW QUALITY OF RIDE

New self-leveling, hydro-gas suspension supports soft ride in harsh conditions.

MANEUVERABILITY

Unique design of rear frame, body, and front-mounted differential and transmission make the Doosan machine the most compact ADT in its class, which results in smallest turning radius and outstanding stability.

DIFFERENTIALS

Front and rear differentials are limited slip, longitudinal differential can be manually locked by pushing 1 button.



SAFETY HIGHLIGHTS

Gradient meter with body flip-over protection, Body Over Centre of Gravity function, fenders and hand rails all around cab, superior stability and always visible and clean front cab access.

BODY

Steel plates with 400 HB hardness. Capacity with/without tailgate : 24.5/26.1 m³. Tailgate, body heating & wear plates available as optional equipment.

DOOSAN **CONNECT** TELEMATICS

Monitor your fleet online. As standard, Doosan Connect system with dual mode (satellite, GSM). Check productivity, fuel consumption, system warnings, maintenance status, etc.

BRAKE SYSTEMS

Oil-cooled wet disc brakes (lifetime up to 15,000 hours). Standard electronic engine brake, hydraulic transmission retarder & parking brake.

SERVICE ACCESSIBILITY

Diesel, AdBlue and grease (for auto-lube system) filling from ground level. Easy access to filters and oil filling points. Tilttable cab with self-positioning locking mechanism.

TOP PERFORMANCE AND FUEL EFFICIENCY

DA30
DA45

THE POWER TO RAISE PRODUCTIVITY

The Doosan ADT concept offers a larger load capacity in all weight categories. Additional load capacity, combined with superior power and traction, improve productivity. The unique advantages of the Doosan ADT's permanent 6-wheel drive, free-swinging rear tandem, front-mounted turning ring, independent front wheel suspension, and sloping rear frame provide excellent driving stability with equal weight distribution and superior traction. The Doosan Articulated Dump Truck is designed to work under very tough conditions and travel up to 55 km/h.



DESIGN SIMPLICITY

Permanent 6-wheel drive, together with the ground-following rear tandem and our special front-mounted turning ring, provide equal power & weight distribution and excellent operating performance. The sloping rear frame provides a lower centre of gravity - improving the ADT's overall stability, and ensuring fast and easy tipping of the body for increased productivity.



Front-mounted articulation hinge

2 limited-slip differentials

1 manual differential lock

Sloping rear frame

Gear-driven tandem axle



ENGINES – LOWER EMISSIONS / SAME GREAT PERFORMANCE

Doosan ADTs use only proven, reliable and powerful diesel Scania engines with excellent torque, which achieve low fuel consumption and fulfill Stage V European regulation requirements.

NEW SELF-LEVELING HYDRO-GAS FRONT SUSPENSION


The DA30's design was based on the successful and proven design of the DA45. It has been upgraded with the self-leveling system for better shock absorption in changing operating conditions.

PAYLOAD METER

Our standard real-life payload & load count meter provides the Doosan operator and owner with an immediate indication of the productivity. External indication lights help load the body more efficient.

DOWNHILL SPEED MODULATION

Powerful hydraulic retarder keeps machine's speed constant on downhills without support of service brakes. Operator can easily adjust the retarder's power by lever or simply pushing the gas pedal.



TRANSPORTABILITY

Thanks to its less than 3-meter width, the DA30 can be moved easily from one site to another. And thanks to the compact design of both machines, a shorter low loader can be used.

FORWARD-MOUNTED TURNING RING

The turning ring is located in front of the articulation point, ensuring equal weight distribution to the front wheels in all operating situations, including maximum turning. The equal weight distribution enables you to use the limited slip differentials with only 45% locking value - ensuring drive to both front wheels in all situations, without completely locking the wheels.

TRACTION

The Doosan ADT's unique design offers permanent 6-wheel drive, ensuring stability and equal weight distribution to accommodate all job applications. The Doosan ADTs superior driveline ensures maximum traction and durability.

* The above image may differ from the actual product.



OPERATE IN COMFORT

DA30
DA45

QUIETEST TRUCK IN THE INDUSTRY

The spacious ROPS/FOPS cab is equipped with climate control and a high-quality operator seat with air suspension to provide excellent comfort. Precise steering, good visibility, low noise levels (72 dB(A), ISO6395) and optional vertical movement provide additional comfort and quiet.

- The sloping hood gives the operator an excellent view
- The cab is mounted on a special rubber suspension to reduce vibration and conduction of noise into the cab



BEST-IN-CLASS OPERATOR ENVIRONMENT

The new DA30 cab was designed based on the feedback received directly from hundreds of Doosan operators. This resulted in upgrade of the cab in features and functions required by the market, including: hand grip on the right side, foot rest, improved storage room, USB charger, Bluetooth radio, all around rails outside the cab, additional lever for retarder control and a number of other new features.

HIGH-COMFORT AIR-SUSPENSION SEAT

Because a highly comfortable seat means a lot to every operator, we provide an air-suspension seat with armrest as standard.

ONE KEY SOLUTION

To enter and safely operate your Doosan ADT, you need just 1 key to lock and unlock all the doors and also start the engine.

SELF-LEVELING, HYDRO-GAS FRONT SUSPENSION

New suspension system has outstanding performance in rough terrain due to big shock absorption capacity of the hydraulic suspension cylinders. On top of that, the self-leveling system can adjust to match changing working conditions.

STORAGE COMPARTMENTS WITH EXTRA 12 V POWER SUPPLY

Plenty of storage spaces, plus extra room designed to fit cool/hot box with additional 12V power supply.

MP3, DAB AND BLUETOOTH

Standard radio supports all modern features like MP3, DAB and Bluetooth

CLIMATE CONTROL


Our specially designed climate control is easy to operate and highly efficient - keeping you comfortable at all times.

* The above image may differ from the actual product.



TOTAL CONTROL IN ALL SIMPLICITY


DA30
DA45



OPERATE AT EASE IN YOUR COMFORT ZONE

The Doosan ADT is one of the industry's simplest trucks to operate and, at the same, time offers a large number of functions. Comfortably seated in this class-leading operator cab, you'll enjoy easy operation combined with excellent efficiency. And thanks to the upgraded monitor panel, you'll operate in your comfort zone.

- Bigger indications
- Multiple languages
- Integrated payload meter (as standard)
- Diagnostic section with transmission and hydraulic oil level check function
- Gradient meter indication for increased safety while operating
- Integrated rear-view camera



LCD COLOR MONITOR PANEL

- 7" color display, resolution 800 x 480 pixels
- Shows all necessary information for driving and handling the machine
- Rear-view camera image embedded in instrumentation graphics
- Backlight dimming according to ambient light conditions
- Sub-menus for additional and diagnostic functions

TOUCH PAD

- Diesel fuel heater ON/OFF
- Longitudinal differential lock
- Override button
- Cab roof and mirror arm front lights ON/OFF
- Rotating beacon ON/OFF (optional)
- Operating work-lights ON/OFF

DIFFERENTIAL ACTIVATION

With automatic limited slip differentials, automatic and manual transmission shift, power steering, "simple touchpad" and "easy to read" display, every ADT is as simple to use & operate as possible.

BODY HOIST LEVER

The new body hoist lever is easy to operate and fingertip controlled. This electronically managed hoist lever incorporates a higher body up speed and an automatic body down feature, with soft touch down, to keep you safe at all times.

"TIP-TRONIC" GEAR SHIFT

To ensure the smoothest possible gear shifts and momentum, you can run the truck in both automatic and manual gears.

RETARDER FORCE MODULATION LEVER

New lever located on the right-hand side below the steering wheel enables operator to choose from 4 power modes. On top of that, the gas pedal is responsible for retarder power reduction.

Body hoist lever with boost button

All-round visibility

* The above image may differ from the actual product.



SIMPLE MAINTENANCE WITH GREAT UPTIME


DA30
DA45

ACCESS MAIN FILLING POINTS WHILE STANDING ON THE GROUND

Improved simplicity of maintenance and service reduces failure rate and improves lifetime and longevity. Convenient position of liquids' levels check and filling points, easy access to filters and very low number of rubber wearing components significantly reduce labor time.



- Easy access to factory-fitted standard automatic central lubrication system
- Dedicated space for grease cartridge and grease gun.
- Easy access to filters
- Diesel and AdBlue filling points accessible from the ground level
- Diesel tank prepared for fast fill coupler
- LED light indicates when power isolator can be switched off
- Power isolator in convenient and safe location
- External power supply



- Multifunctional display with available service/maintenance functions
- Transmission oil level check
- Status of hydraulic and electronic components

TRAINING CENTER

Located in the heart of Europe, near Prague (Czech Republic), the Doosan Academy is a dynamic center of knowledge where Product, Service and Doosan University training courses are held.

The facilities include a modern building that can accommodate all of the product ranges, and an outdoor training area where we conduct field exercises and product testing with the fleet of Doosan machines and attachments.

FILTERS

All filters are centralized for quicker and easier accessibility.

GLOBAL DOOSAN NETWORK

With a network of Doosan Dealers & Parts Distribution Centers worldwide, your Doosan trucks can be serviced & maintained wherever you are.

TELEMATICS

The Doosan Connect system is available for reading out vehicle operating & production parameters remotely, and providing you with total ease-of-mind. Keep day-by-day overview on the machine's productivity, status and condition.





TELEMATICS SERVICE (OPTIONAL)



GLOBAL PARTS NETWORK

TELECOMMUNICATIONS

Data flow from machine to web



TELEMATICS SERVICE TERMINAL




Telematics Service terminal is installed to machine / connected to EPOS™



TELECOMMUNICATION



GPS, EPOS™ data is sent to designated server by GSM, Satellite telecommunication



DOOSAN TELEMATICS SERVICE WEB



Doosan, Dealer, Customer can easily monitor the GPS, EPOS™ data from Core Telematics Service web

BENEFITS




JOB SITE MANAGEMENT

FUNCTIONS

Location

- GPS
- Geo-fence



Reports

- Periodic operation report
- Utilization



WORK EFFICIENCY MANAGEMENT


Operation Trend

- Total operation hour
- Operation hour by mode



Fuel Efficiency*

- Fuel level
- Fuel consumption



PREVENTIVE MAINTENANCE

Filter & Oil Management

- Preventive maintenance by item replacement cycle


Item	Filter	Oil	Water	Other
Excavator	200.4	200.4	200.4	200.4
Excavator	431	431	431	431
Excavator	210.3	210.3	210.3	210.3
Excavator	83.2	83.2	83.2	83.2
Excavator	240.3	240.3	240.3	240.3



PROACTIVE SERVICE

Warning & Alert

- Detect machine warnings
- Antenna disconnection
- Geo/Time fence



* Functions may not be applied to all models. Please contact your sales representative to get more information of the service.

TELEMATICS SERVICE BENEFITS

Customer

- Improve work efficiency
- Timely and preventive service
- Improve operator's skills by comparing work pattern
- Manage fleet more effectively

Dealer


- Better service for customers
- Provide better quality of service
- Maintain machine value
- Better understanding of market needs

Doosan

- Responsive to customer's voice
- Utilize quality-related field data
- Apply customer's usage profile to developing new machine

GLOBAL PDC (PARTS DISTRIBUTION CENTER) NETWORK

Doosan provides fast and precise worldwide delivery of genuine Doosan parts through its global PDC (parts distribution center) network.



GLOBAL NETWORK

The global network of the GPDC (Global Parts Distribution Center) maximizes its supply rate by making sure that each center is stockpiled with all the critical parts required for businesses in its area. The network also minimizes the time and costs required for parts delivery by positioning PDCs close to major markets around the world. Doosan PDCs communicate with customers in their time zone, informing them that they are open for operation, and deliver parts to them as early as possible.

The Global Parts

Distribution Center Network

PDCs had been set up as shown below, including Mother PDC in Ansan, Korea. The eight other PDCs include one in China (Yantai), two in the USA (Chicago and Miami), one in Brazil (Campinas), two in Europe (Germany and the UK), one in the Middle East (Dubai), and one in Asia (Singapore).



MPDC : Mother Parts Distribution Center

PDC : Parts Distribution Center

PDC BENEFIT



Distribution Cost Reduction



Maximum Parts supply rate



Shortest distance/time parts delivery



Real-time service support



Minimum downtime

TECHNICAL SPECIFICATIONS

DA30

BODY

Body volume (With tailgate)
16.8 m³ – 22.0yd³
Material
Hardened abrasion-resistant steel plates (400 HB)
Tilt cylinders
Single stage, double-acting
Tipping time
Up : 12 sec. / Down : 10 sec.
Body
Designed for exhaust heating
Sloping frame
Down from the hinge point
Level capacity (with/without tailgate)
14.2 m³ / 13.6 m³ – 18.6 yd³ / 17.8 yd³
Heaped capacity (with/without tailgate)
17.8 m³ / 16.8 m³ – 23.3 yd³ / 22.0 yd³

ELECTRICAL SYSTEM

Batteries
2 x 12V 140 Ah (series connected to give 24V)
Starter
8 HP (6 kW)
Alternator
24 V 100 A

WEIGHTS

Empty : Front axle
12500 kg – 27558 lb
Empty : Rear axle
10600 kg – 23369 lb
Max. admissable axle load: Front axle
16700 kg – 36817 lb
Max. admissable axle load: Rear axle
37000 kg – 81571 lb
Max. admissable weight
51500 kg – 113538 lb
Payload
28 metric ton – 31 short ton
Net weight
23100 kg – 50928 lb
NOTE: All weights include a full fuel tank and operator

POWER TO WEIGHT RATIO (NET POWER VS TON)

Empty
11.9 kW/t
Loaded
5.4 kW/t

GROUND PRESSURE

Ground pressure
Standard 23.5 x 25 tyres with 15% sinkage
Empty : Front axle
121.7 kPa – 17.65 psi
Empty : Rear axle
51.6 kPa – 7.48 psi
Loaded : Front axle
161.6 kPa – 23.44 psi
Loaded : Rear axle
169.8 kPa – 24.63 psi

CAPACITIES

Fuel tank
360 l
Hydraulic system
75 l
Adblue tank
70 l
Hub front
11
Tandem housing, rear differential and hubs
145,3
Cooling circuit
35
ENGINE
35

ENGINE

Complies with Tier II for emissions
Scania DC 9, water-cooled, diesel engine with turbo charger and air-to-air intercooler
Power rating ISO 3046 / ISO 14396 @ 2100 rpm
375 HP (276 kW) / 362 HP (270 kW)
No. of cylinders
5 (in line)
Gross torque
1830Nm @1200rpm
Cylinder volume
9.3 litres
Bore diameter x stroke
130 x 140 mm
Air filter
Dry type

SPEEDS

Speeds
Forward – Reverse
Forward 1 – 2 – 3 – 4 – 5 – 6 – 7 – 8
6 - 8 - 11 - 16 - 23 - 32 - 45 - 55 km/h
Reverse 1 – 2 – 3 – 4
6 - 8 - 11 - 16 km/h
TRANSMISSION
Electronically-controlled automatic transmission with retarder. The torque converter has automatic lock-up in all gears.
ZF 8 EP320

HYDRAULIC SYSTEM

1 variable displacement piston pump for steering & tipping for cooling fan, brakes & auxiliaries
305 l/min @ 2100 rpm
Filtration
One return flow filter
Main safety valves pressures, tipping/steering circuit
280 / 210 bar

TIRES

Standard
23.5 R25 two star radial

TECHNICAL SPECIFICATIONS

DA45

BODY

Body volume (With tailgate)
24.6m³ – 31.9 yd³
Material
Hardened abrasion-resistant steel plates (400 HB)
Tilt cylinders
Single stage, double-acting
Tipping time
Up: 12 sec. / Down: 10 sec.
Body
Designed for exhaust heating
Sloping frame
Down from the hinge point
Level capacity (with/without tailgate)
20.4 m³ / 19.6 m³ – 26.7 yd³ / 25.6 yd³
Heaped capacity (with/without tailgate)
26.1 m³ / 24.6 m³ – 47.1 yd³ / 31.9 yd³

ELECTRICAL SYSTEM

Batteries
2 x 12V 140 Ah (series connected to give 24V)
Starter
8 HP (6 kW)
Alternator
24 V 100 A

WEIGHTS

Empty : Front axle
14500 kg – 31967 lb
Empty : Rear axle
16000 kg – 35274 lb
Max. admissable axle load: Front axle
22500 kg – 49604 lb
Max. admissable axle load: Rear axle
55000 kg – 121254 lb
Max. admissable weight
71500 kg – 157631 lb
Payload
41 metric ton – 45short ton
Net weight
30500 kg – 67241 lb
NOTE: All weights include a full fuel tank and operator

POWER TO WEIGHT RATIO (NET POWER VS TON)

Empty
11.8 kW/t
Loaded
5.0 kW/t

GROUND PRESSURE

Ground pressure
Standard 29.5 x 25 tyres with 15 % sinkage
Empty : Front axle
93.9 kPa – 13.62 psi
Empty : Rear axle
51.8 kPa – 7.51 psi
Loaded : Front axle
139.2 kPa – 20.19 psi
Loaded : Rear axle
161.3 kPa – 23.39 psi

CAPACITIES

Fuel tank
500 l
Hydraulic system
85 l
Adblue tank
70 l
Hub front
9,6
Tandem housing, rear differential and hubs
228
Cooling circuit
35
ENGINE
45

ENGINE

Complies with Tier II for emissions
Scania DC 13, water-cooled, diesel engine with turbo charger and air-to-air intercooler
Power rating ISO 3046 / ISO 14396 @ 2100 rpm
500 hp (368 kW) / 483 hp (360 kW)
No. of cylinders
6 (in line)
Gross torque
2300 Nm @ 1200 rpm
Cylinder volume
12.7 litres
Bore diameter x stroke
130 x 160 mm
Air filter
Dry type

SPEEDS

Speeds
Forward – Reverse
Forward 1 – 2 – 3 – 4 – 5 – 6 – 7 – 8
5 - 8 - 11 - 16 - 23 - 32 - 45 - 55 km/h
Reverse 1 – 2 – 3 – 4
5 - 8 - 11 - 16 km/h

TRANSMISSION

Electronically-controlled automatic transmission with retarder. The torque converter has automatic lock-up in all gears.
ZF 8 EP420

HYDRAULIC SYSTEM

1 variable displacement piston pump for steering & tipping for cooling fan, brakes & auxiliaries
305 l/min @ 2100 rpm
Filtration
One return flow filter
Main safety valves pressures, tipping/steering circuit
280 / 210 bar

TIRES

Standard
29.5 R25 two star radial

SPECIAL FEATURES

DA30/DA45 SPECIAL FEATURES

Suspension

- Front: Semi-independent, self-leveling hydro-gas suspension.
- Rear: Free-swinging tandem housing.

Articulation hinge and steering

- Articulation hinge with forward-mounted turning ring.
- Steering cylinders (two): Double-acting.
- The steering is approved according to ISO 5010.
- Max. steering angle : 45°.
- Ground-driven emergency steering pump.

Driveline

- Full-time 6 x 6 drive with two transverse differentials and one longitudinal.
- Front axle transverse differential :
Limited-slip diff lock with 45% locking ratio.
- Rear axle transverse differential :
Limited-slip diff lock with 45% locking ratio.
- Inter-axle longitudinal differential :
 - Torque-proportioning differential, integrated into the ZF transmission.
 - Torque distribution :
 - 1/3 to the front axle
 - 2/3 to the rear axle
 - 100 % lockable
- Tandem housing: Gear driven, free - swinging Provides equal drive to rear wheels and ensures the best possible ground contact – whatever the ground conditions.

Brake system


- Dual circuit braking system acting on all six wheels.
- Approved according to ISO 3450.
- All hydraulic-operated brakes with enclosed oil-cooled wet multiple discs on four hubs (braking force distributed to two hubs by tandem gear wheels)
- Spring actuated hydraulic released parking brake, mounted on driveline shaft.
- Max. gradient, parking brake : 20 °.
- Automatic transmission retarder as standard.

Cab


- Approved to ROPS/FOPS standards (ISO 3471, ISO 3449).
- Low interior sound level : 71 dB(A) (ISO 6395).
- External sound level : 108 dB(A) (ISO 6396).
- The cab is centrally located on rubber mountings.
- Hand and arm vibrations are less than 2.5 ms² (ISO 5349-2).
- Whole body vibration is less than 0.5 ms² according to ISO 2631-1.
- Superior visibility – for safer operation.
- Superior operating controls location.
- Adjustable suspended operator seat.
- Adjustable steering column.
- Climate control – Heater and air conditioning.
- Tilting for service access.
- All-around hand rails.

DIMENSIONS

DA30



DA45



STANDARD AND OPTIONAL EQUIPMENT

STANDARD EQUIPMENT


Engine
• Scania, Complies with Tier II for emissions, water-cooled, diesel engine with VGT turbo charger and air-to-air intercooler
Hydraulic System
• 1 variable displacement piston pump for steering & tipping • One return flow filter
Safety
• Gradient meter with anti-flip-over protection system • Payload meter & cycle counter • Wet disc brake • Rear-view camera • Hammer for emergency escape • Hand rails on the fenders
Other
• Transmission retarder brake • Automatic lubrication system • Mud flaps • Towing hook, front and rear • Doosan Connect Telematic system • Work light kit (rear and front)

Cab & Interior
• Armrest at operator seat • Headrest at operator seat • Safety belt at operator and instructor seat • Adjustable steering column • All instrumentation in LCD display • Cigarette lighter • 12 V and USB charging point • Retractable roller sunblind • Tinted safety glass • Sliding window (left & right side) • Windshield wiper and washer • Side mirrors • Protection for rear window • Emergency steering, ground-driven • Radio/MP3 and Bluetooth • Cab tilting system • Emergency shutdown switch • Anti-slip steps & platform • Cool box compartment • Storage room • Electronic climate control • High-comfort seat (vertical and longitudinal suspension) • Heated operator seat • Heated mirror • Electrically adjustable mirrors

OPTIONAL EQUIPMENT

Other
• Tail gate • Webasto heating system (heat up the cooling system) • Electrical engine heater • Fire extinguisher • First aid kit • Beacon • Light bar • Speed limitation • Work light kit (rear and front) LED • Tool kit • Warning triangle • Fast fill • Tire pressure monitoring system (may not be available with all tires) • Electric diesel refueling pump
Safety
• Seat belt green warning light • Blue or orange flashing reverse light • White noise alarm
Tires options
• Quarry • Earthmoving • Flotation tires

Some of these options may be standard in some markets. Some of these options may not be available for certain markets. Please check with your local DOOSAN dealer for more information about availability or to adapt your machine to your application needs.



Doosan is

Since 1896, Doosan, the oldest company in Korea, has evolved with its people. The company grew up rapidly for last 10 years with reputation. For human-oriented vision, Doosan has been building constructions, energy, machines, infra structures globally. As a global leader of infra structure, Doosan continues its vision to make human-oriented future.

First in Korea, Doosan self-developed excavators in 1985 and continued building versatile construction machines including excavators, wheel loaders, articulated dump trucks to execute its human-oriented philosophy. Doosan became a global leader of heavy construction machine industry by achieving global sales line, producing line, and distribution line. Along with large production bases in Korea, China, USA, Czech, Brazil, Doosan has 1400 dealer networks and Doosan is providing reliable products and trusted solutions for your stable business at no risk.



DIPBE-00-1910



Doosan Infracore Co., Ltd.
489 (Hwasu-dong), Injung-ro, Dong-Gu,
Incheon, Korea(22502)
www.doosaninfracore.com/ce/

Copyright 2019. Doosan Infracore. All rights reserved.